



**Specifications Bright Choice LED  
Downlight Round Tilttable 12W 960lm  
60D - 930 Warm White | 110mm -  
Cutout 90mm - UGR <19**

[View Product](#)

## General Information

|                          |                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------|
| SKU                      | 245188                                                                                    |
| EAN                      | 8719157041867                                                                             |
| Brand                    | Bright Choice                                                                             |
| Manufacturer Name        | White label LED Downlight Round Tilttable 12W 960lm 60D 930 UGR19 CutoutØ90mm FrameØ110mm |
| Any Lamp all-in warranty | 2 Years                                                                                   |
| Average Lifetime (h)     | 20000                                                                                     |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tilttable                   | Yes               |
| Technology                  | LED Integrated    |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 930 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 90-99             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Beam Angle (degree)         | 60                |
| Luminous Efficacy (lm/W)    | 80                |

|                         |                                |
|-------------------------|--------------------------------|
| Installation Depth (mm) | 75                             |
| Unified Glare Rating    | < 19 - for offices and schools |
| Product Type Category   | LED Downlight                  |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 90                |
| IP-rating              | IP20              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature  | -20 to +40        |
| Colour of the Fixture  | White             |
| Colour of material     | White             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 75  |
| Diameter (mm) | 110 |

## Sensor Information

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

## Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

