



**Specifications Noxion LED Panel Delta Value V5 28W 3920lm - 830-840 CCT | 60x60cm - UGR<19 - Backlit - TRIAC Dimmable**

[View Product](#)

## General Information

|                          |                                                                                     |
|--------------------------|-------------------------------------------------------------------------------------|
| SKU                      | 255285                                                                              |
| EAN                      | 8719157066440                                                                       |
| Brand                    | Noxion                                                                              |
| Manufacturer Name        | Noxion LED Panel Delta Value V5.1 28W 3920lm 2CCT 600*600 UGR<19 Backlit - TRIAC di |
| Any Lamp all-in warranty | 6 Years                                                                             |
| Average Lifetime (h)     | 90000                                                                               |
| Series                   | Delta Value                                                                         |

## Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Technology                  | LED Integrated                   |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Dimmable                         |
| Colour Code                 | 830 Warm White, 840 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                            |
| Colour of Light             | White                            |
| Light colour options        | CCT                              |
| Luminous Efficacy (lm/W)    | 140                              |
| IP-rating                   | IP20                             |
| Impact Protection (IK)      | IK02 - 0.20 joule                |

|                       |               |
|-----------------------|---------------|
| Fixture Connection    | Push Terminal |
| Finish of Reflector   | Frosted       |
| Power factor          | >0.90         |
| Product Type Category | LED Panel     |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -20 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 32      |

## Sensor Information

Type of sensor No Sensor

**Why Any-lamp?**



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

