



**Specifications Philips LED Panel  
TrueBlend 28.5W 3600lm - 940 Cool  
White | 120x30cm - UGR < 16 - Best  
Colour Rendering - Dimmable - Motion  
and Light Sensor - Emergency 3H**

[View Product](#)

## General Information

|                          |                                          |
|--------------------------|------------------------------------------|
| SKU                      | 251918                                   |
| EAN                      | 8720169622005                            |
| Brand                    | Philips                                  |
| Manufacturer Name        | RC453B 36S/940 DLO9010U4ELW3L1200W300B30 |
| Any Lamp all-in warranty | 5 Years                                  |
| Average Lifetime (h)     | 50000                                    |

## Technical Information

|                             |                                        |
|-----------------------------|----------------------------------------|
| Technology                  | LED Integrated                         |
| Voltage (V)                 | 220-240                                |
| Dimmable                    | Dimmable when using a Dimmable Ballast |
| Colour Code                 | 940 Cool White                         |
| Colour temperature (Kelvin) | 4000 Cool White                        |
| Colour Rendering (Ra)       | 90-99                                  |
| Colour of Light             | White                                  |
| Light colour options        | Single Color                           |
| Luminous Efficacy (lm/W)    | 126                                    |
| IP-rating                   | IP20                                   |
| Impact Protection (IK)      | IK03 - 0.35 joule                      |
| Fixture Connection          | Screwless terminal                     |

|              |       |
|--------------|-------|
| Power factor | >0.90 |
|--------------|-------|

|                       |           |
|-----------------------|-----------|
| Product Type Category | LED Panel |
|-----------------------|-----------|

## Fixture Information

|                 |          |
|-----------------|----------|
| Mounting Method | Recessed |
|-----------------|----------|

|                      |                                |
|----------------------|--------------------------------|
| Unified Glare Rating | < 16 - for offices and schools |
|----------------------|--------------------------------|

|               |                    |
|---------------|--------------------|
| Optical Cover | PC (Polycarbonate) |
|---------------|--------------------|

|                       |          |
|-----------------------|----------|
| Operating Temperature | 0 to +25 |
|-----------------------|----------|

|                    |                    |
|--------------------|--------------------|
| Emergency Lighting | 3H Emergency Light |
|--------------------|--------------------|

|                       |       |
|-----------------------|-------|
| Colour of the Fixture | White |
|-----------------------|-------|

|         |       |
|---------|-------|
| Housing | Steel |
|---------|-------|

|                    |       |
|--------------------|-------|
| Colour of material | White |
|--------------------|-------|

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
|----------------|----------|

|             |      |
|-------------|------|
| Length (mm) | 1200 |
|-------------|------|

|            |     |
|------------|-----|
| Width (mm) | 300 |
|------------|-----|

|             |    |
|-------------|----|
| Height (mm) | 75 |
|-------------|----|

## Sensor Information

|                |                             |
|----------------|-----------------------------|
| Type of sensor | Light Sensor, Motion Sensor |
|----------------|-----------------------------|

## Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

